

Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001



Cert. No.: 4354-12147706

Traceable® Certificate of Calibration for Extra-Long-Stem Thermometer

Manufactured for and distributed by: Thomas Scientific Box 99,99 High Hill Road, Swedeboro, NJ, 08085-0099, U.S.A.

1725

Instrument Identification:

Model: 9329H07,

S/N: 210298779

Manufacturer: Control Company

andards/Equipment:									
Description	Serial Number	<u>Due Date</u>	NIST Traceable Reference						
Temperature Calibration Bath	A73332								
Temperature Calibration Bath	B3A444								
Thermistor Module	B96381	21 Aug 2021	1000457544						
Temperature Probe	5392	04 Aug 2021	C0804052						
Temperature Probe	5398	04 Aug 2021	C0804051						

Certificate Information:

Technician: 420

Procedure: CAL-03

Cal Date: 13 Apr 2021

Cal Due Date: 13 Apr 2023

Test Conditions: 56.6

56.65%RH 22.4°C 1015mBar

Calibration Data: (New Instrument)

Unit(s)	Nominal	As Found	In Tol	Nominal	As Left	In Tol	Min	Max	±U	TUR
°C	N.A.	N.A.		0.00	0.1	Y	-0.5	0.5	0.058	>4:1
°C	N.A.	N.A.		100.00	100.2	Y	99.5	100.5	0.058	>4:1

This certificate indicates Traceability to standards provided by (NIST) National Institute of Standards and Technology and/or a National Standards Laboratory.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement: (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 95% confidence level. In tolerance conditions are based on test results falling within specified limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal=Standard's Reading; As Left=Instrument's Reading; In Tol=In Tolerance; Min/Max=Acceptance Range; ± U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=±(Max-Min)/2; Min=As Left Nominal(Rounded) – Tolerance; Max= As Left Nominal(Rounded) + Tolerance;

Rich Rodriguez

Nicol Rodriguez, Quality Manager

Marisa Elms, Technical Manager

Note:

Maintaining Accuracy:

In our opinion once calibrated your Extra-Long-Stem Thermometer should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Extra-Long-Stem Thermometer change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contact Control Company.

Issue Date: 13 Apr 2021