

Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001



Cert. No.: 4354-12899009

Traceable® Certificate of Calibration for Extra-Long-Stem Thermometer

Manufactured for and distributed by: Thomas Scientific Box 99,99 High Hill Road, Swedeboro, NJ, 08085-0099, U.S.A.

Instrument Identification:

Model: 9329H07,

S/N: 211047627

Manufacturer: Control Company

Standards/Equipment:

Description	Serial Number	Due Date		NIST Traceable Reference		
Temperature Calibration Bath	93139					
Temperature Probe	128		09 Jul 2022	15-D4F0Q-40-1		
Thermistor Module	A17118		08 Jul 2022	1000469276		
Temperature Probe	3039		09 Jul 2022	15-D4F0Q-20-1		
Temperature Calibration Bath	B3A444					

Certificate Information:

Technician: 420

Procedure: CAL-03

Cal Date: 07 Dec 2021

Cal Due Date: 07 Dec 2023

Test Conditions: 52.62%RH 23.71°C 1020mBar

Calibration Data: (New Instrument)

Unit(s)	Nominal	As Found	In Tol	Nominal	As Left	In Tol	Min	Max	±U	TUR
°C	N.A.	N.A.		0.00	0.0	Υ	-0.5	0.5	0.058	>4:1
°C	N.A.	N.A.		100.00	100.0	Y	99.5	100.5	0.058	>4:1

This certificate indicates Traceability to standards provided by (NIST) National Institute of Standards and Technology and/or a National Standards Laboratory.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement: (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 95% confidence level. In tolerance conditions are based on test results falling within specified limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal=Standard's Reading; As Left=Instrument's Reading; In Tol=In Tolerance; Min/Max=Acceptance Range; ± U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=±(Max-Min)/2; Min=As Left Nominal(Rounded) – Tolerance; Max= As Left Nominal(Rounded) + Tolerance;

Rial Rodriguez

Nicol Rodriguez, Quality Manager

Marisa Elms, Technical Manager

Note:

Maintaining Accuracy:

In our opinion once calibrated your Extra-Long-Stem Thermometer should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Extra-Long-Stem Thermometer change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contact Control Company.

Issue Date : 07 Dec 2021

CONTROL COMPANY 12554 Galveston RD Suite B230 Webster TX USA 77598
Phone 281 482-1714 Fax 281 482-9448 sales@control3.com www.traceable.com