

Calibration complies with ISO/IEC 17025, ANSI/NCSL Z540-1, and 9001

3

Cert. No.: 1042-14568153

Traceable® Certificate of Calibration for Waterproof/Shockproof Stopwatch

Manufactured for and distributed by: Traceable® Products 12554 Galveston Rd B230, Webster, TX 77598

1754

Instrument Identification:

Model: 1042,94460-55

S/N: 230728636

Manufacturer: Control Company

Standards/Equipment:

Description

Serial Number

Due Date

NIST Traceable Reference

Non-Contact Frequency Counter

26.66887

10 Jul 2024

1000493638

Certificate Information:

Technician: 447

Procedure: CAL-01

Cal Date: 31 Oct 2023

Cal Due Date: 31 Oct 2025

Test Conditions: 41.66%RH 23.96°C 1028mBar

Calibration Data: (New Instrument)

Unit(s)	Nominal	As Found	In Tol	Nominal	As Left	In Tol	Min	Max	±U	TUR
sec/24hr	N.A.	N.A.		0.000	0.600	Υ	-8.64	8.64	0.041	>4:1

This certificate indicates Traceability to standards provided by (NIST) National Institute of Standards and Technology and/or a National Standards Laboratory.

A Test Uncertainty Ratio of at least 4:1 is maintained unless otherwise stated and is calculated using the expanded measurement uncertainty. Uncertainty evaluation includes the instrument under test and is calculated in accordance with the ISO "Guide to the Expression of Uncertainty in Measurement: (GUM). The uncertainty represents an expanded uncertainty using a coverage factor k=2 to approximate a 95% confidence level. In tolerance conditions are based on test results falling within specified limits with no reduction by the uncertainty of the measurement. The results contained herein relate only to the item calibrated. This certificate shall not be reproduced except in full, without written approval of Control Company.

Nominal=Standard's Reading; As Left=Instrument's Reading; In Tol=In Tolerance; Min/Max=Acceptance Range; ± U=Expanded Measurement Uncertainty; TUR=Test Uncertainty Ratio; Accuracy=±(Max-Min)/2; Min=As Left Nominal(Rounded) – Tolerance; Max= As Left Nominal(Rounded) + Tolerance;

Rid Rossique

Nicol Rodriguez, Quality Manager

Note:

Maintaining Accuracy:

In our opinion once calibrated your Waterproof/Shockproof Stopwatch should maintain its accuracy. There is no exact way to determine how long calibration will be maintained. Waterproof/Shockproof Stopwatch change little, if any at all, but can be affected by aging, temperature, shock, and contamination.

Recalibration:

For factory calibration and re-certification traceable to National Institute of Standards and Technology contact Control Company.

Issue Date: 31 Oct 2023